UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/650,792	08/29/2003	Sung-Kyung Jang	P-0577	1879
34610 KED & ASSOC	7590 07/02/200 CIATES, LLP	EXAMINER		
P.O. Box 22120	00	ROBERTS, BRIAN S		
Chantilly, VA 20153-1200			ART UNIT	PAPER NUMBER
			2619	
			MAIL DATE	DELIVERY MODE
			07/02/2008	PAPER

# Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)				
	10/650,792	JANG, SUNG-KYUNG				
Office Action Summary	Examiner	Art Unit				
	BRIAN ROBERTS	2619				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply						
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.  - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.  - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).						
Status						
1) Responsive to communication(s) filed on 27 Ma	av 2008.					
	·_ · · · · · · · · · · · · · · · · · ·					
·=						
	closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.					
Disposition of Claims						
4)⊠ Claim(s) <u>1-35</u> is/are pending in the application.						
4a) Of the above claim(s) is/are withdrawn from consideration.						
5) Claim(s) is/are allowed.						
6)⊠ Claim(s) <u>1-35</u> is/are rejected.						
7) Claim(s) is/are objected to.						
8) Claim(s) are subject to restriction and/or	election requirement.					
Application Papers						
9) The specification is objected to by the Examiner.						
10) The drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner.						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).						
11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.						
Priority under 35 U.S.C. § 119						
<ul> <li>12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a) All b) Some color None of:</li> <li>1. Certified copies of the priority documents have been received.</li> <li>2. Certified copies of the priority documents have been received in Application No.</li> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>						
Attachment(s)						
1) Notice of References Cited (PTO-892)	4) Interview Summary					
2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08)	Paper No(s)/Mail Da 5) Notice of Informal Pa					
Paper No(s)/Mail Date 6)  Other:						

# **DETAILED ACTION**

Claims 1-35 remain pending.

### Continued Examination Under 37 CFR 1.114

A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 05/27/2008 has been entered.

# Claim Rejections - 35 USC § 112

The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

Claims 1-35 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the enablement requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to enable one skilled in the art to which it pertains, or with which it is most nearly connected, to make and/or use the invention. Independent claim 1, and similarly in independent claims 11 and 22, recites the limitation "the window size control information includes window size upward setting information, window size maintaining information, window size downward setting

information". The limitation is not enabled by the disclosure because the window size control information can only include one of the types of information and not all three types. The Examiner recommends amending the limitation to recite that the window size control information includes either window size upward setting information, window size maintaining information, or window size downward setting information. The dependent claims are rejected as being dependent on the rejected independent claims.

# Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 1-35, as best understood, are rejected under 35 U.S.C. 103(a) as being unpatentable over ETSI TS 125 322 version 5.1.0 (2002-06) in view of Le et al. (US 6744730)

- In reference to claim 1

In Figure 4.4 and 9.10, ETSI TS 125 322 teaches a data transfer controlling method in a radio system which transmits and receives data in an acknowledgement mode that includes receiving data units having serial numbers lying in a range of a receiving window (pg. 27 9.2.2.3), transmitting window size control information (pg. 33 9.2.2.11.3) from a receiver to a transmitter and varying a transmitting window size by the transmitter according to the transmitted window size control information wherein the

window size information includes either window size upward setting information, window size maintaining information, or window size downward setting information (pg. 33 9.2.2.11.3) and is transmitted simultaneously with acknowledgement information (pg. 32 9.2.2.11.2).

ETSI TS 125 322 does not explicitly teach transmitting window size control information from a receiver to a transmitter by a state of a receiving buffer.

In Figure 1, Le et al. teaches transmitting window size control information from a receiving host (18) to a sending host (10) based on a state of a receiving buffer that corresponds to the a receiving window. The receiving host (18) instructs the sending host (10) to increase the window size when the receiving buffer is near empty and instructs the sending host (10) to decrease the window size when the receiving buffer is near full. (column 2 lines 23-41)

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the data unit containing the acknowledgement information of ETSI TS 125 322 to include transmitting window size control information from a receiver to a transmitter by a state of a receiving buffer that corresponds to a receiving window as suggested by Le et al. because it allows the window size data transmission rate to be varied in order to prevent buffer overflow or under utilization of network resources.

## - In reference to claim 2

In Figure 4.4, ETSI TS 125 322 further teaches the transmitter is a network and the receiver is a terminal. (pg. 15 4.2.1.3.1 .; 4.2.1.3.2)

Art Unit: 2619

- In reference to claim 3, 14, 27

In Figure 9.10, ETSI TS 125 322 further teaches the window size control information is contained in status information to be transmitted. (pg. 33 9.2.2.11.3)

- In reference to claim 4, 26

In Figure 9.10, ETSI TS 125 322 further teaches the window size control information is a window size super-field (SUFI). (pg. 33 9.2.2.11.3)

- In reference to claim 5 16, 28-29

In Figure 9.10, ETSI TS 125 322 further teaches the status information further includes an ACK SUFI. (pg 31 9.2.2.11)

- In reference toclaim 6, 13, 23

In Figure 9.10, ETSI TS 125 322 further teaches the receiver adjusts a receiving window size to be the same as the transmitting window size. (pg. 33 9.2.2.11.3)

- In reference to claim 7, 8, 17-19, 24-25

ETSI TS 125 322 teaches a system and method that covers substantially all limitations of the parent claim.

ETSI TS 125 322 does not teach the window size control information includes window size downward setting information if a receiving buffer is in an overflow state.

In Figure 1, Le et al. teaches transmitting window size control information from a receiving host (18) to a sending host (10) based on a state of a receiving buffer. The receiving host (18) instructs the sending host (10) to increase the window size when the receiving buffer is near empty and instructs the sending host (10) to decrease the window size when the receiving buffer is near full. (column 2 lines 23-41)

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the window size control information of ETSLTS 125 322 to include window size downward setting information if a receiving buffer is in an overflow state as suggested by Le et al. because it allows the window size to be varied in order to prevent buffer overflow.

- In reference to claim 9, 10, 20-21, 30-31

ETSI TS 125 322 teaches a system and method that covers substantially all limitations of the parent claim.

ETSI TS 125 322 does not teach the window size control information includes window size upward setting information if a receiving buffer is not in an overflow state.

In Figure 1, Le et al. teaches transmitting window size control information from a receiving host (18) to a sending host (10) based on a state of a receiving buffer. The receiving host (18) instructs the sending host (10) to increase the window size when the receiving buffer is near empty and instructs the sending host (10) to decrease the window size when the receiving buffer is near full. (column 2 lines 23-41)

Art Unit: 2619

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the window Size control information of ETSI TS 125 322 to include window size upward setting information if a receiving buffer is not in an overflow state as suggested by Le et al. because it allows the window size to be varied in order to prevent utilization of network resources.

#### - In reference to claim 11

In Figure 4.4 and 9.10, ETSI TS 125 322 teaches a data transfer controlling method in a radio system which controls a flow of a radio link and includes an entity operated in an acknowledgement mode, wherein window size update information (pg. 33 9.2.2.11.3) is transmitted from a receiving entity to a transmitting wherein acknowledgement information (pg. 32 9.2.2.11.2) is transmitted simultaneously with the window size control information, the acknowledgement information controlling transmission of additional data units from the transmitter to the receiver, transmission of the additional data units controlled based on window size update information(pg. 15 4.2.1.3.1.; 4.2.1.3.2) wherein the window sized control information includes includes either window size upward setting information, window size maintaining information, or window size downward setting information (pg. 33 9.2.2.11.3)

ETSI TS 125 322 does not teach transmitting window size control information from a receiver to a transmitter by a state or processing speed by the receiver of data units stored in a receiving buffer.

In Figure 1, Le et al. teaches transmitting window size control information from a receiving host (18) to a sending host (10) based on a state of a receiving buffer. The receiving host (18) instructs the sending host (10) to increase the window size when the receiving buffer is near empty and instructs the sending host (10) to decrease the window size when the receiving buffer is near full. (column 2 lines 23-41)

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the data unit containing the acknowledgement information of ETSI TS 125 322 to include transmitting window size control information from a receiver to a transmitter by a state of a receiving buffer as suggested by Le et al. because it allows the window size data transmission rate to be varied in order to prevent buffer overflow or under utilization of network resources.

- In reference to claim 12

In Figure 4.4, ETSI TS 125 322 further teaches the entity is a radio link control (RLC). (pg. 15 4.2.1.3.1.; 4.2.1.3.2)

- In reference to claim 15

In Figure 9.10, ETSI TS 125 322 further teaches the window size update information is included in a window size super-field (SUFI). (pg. 33 9.2.2.11.3)

In reference to claim 22

Page 9

Art Unit: 2619

In Figure 4.4 and 9.10, ETSI TS 125 322 teaches a data transfer controlling method in a radio data transfer of a mobile communication system that includes receiving atleast one protocol data unit (PDU) from a transmitting RLC entity; transmitting window size control (pg. 33 9.2.2.11.3) to the transmitting RLC entity and varying a transmitting window size according to the window size control information by the transmitting RLC entity and transmitting additional PDUs to be stored in a receiving buffer wherein acknowledgement information (pg. 32 9.2.2.11.2) is transmitted simultaneously with the window size control information, the acknowledgement information controlling transmission of additional PDUs based on the varied transmitting window (pg. 15 4.2.1.3.1.; 4.2.1.3.2) includes either window size upward setting information, window size maintaining information, window size downward setting information (pg. 33 9.2.2.11.3).

ETSI TS 125 322 does not teach transmitting window size control information from a receiver to a transmitter by a state of a receiving buffer.

In Figure 1, Le et al. teaches transmitting window size control information from a receiving host (18) to a sending host (10) based on a state of a receiving buffer. The receiving host (18) instructs the sending host (10) to increase the window size when the receiving buffer is near empty and instructs the sending host (10) to decrease the window size when the receiving buffer is near full. (column 2 lines 23-41)

It would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the data unit containing the acknowledgement information of ETSI TS 125 322 to include transmitting window size control information from a receiver

Art Unit: 2619

to a transmitter by a state of a receiving buffer as suggested by Le et al. because it allows the window size and data transmission rate to be varied in order to prevent buffer overflow or under utilization of network resources.

## - In reference to claim 32

The combination of ETSI TS 125 322 and Le et al. teaches a system and method that substantially covers all limitations of the parent claims. ETSI TS 125 322 further teaches the acknowledgement information is included in a first super-field (pg. 32 9.2.2.11.2 and the window size control information is included in a second super-field (pg. 33 9.2.2.11.3) within a status PDU from the receiver to the transmitter. (pg. 15 4.2.1.3.1.; 4.2.1.3.2)

## In reference to claim 33

The combination of ETSI TS 125 322 and Le et al. teaches a system and method that substantially covers all limitations of the parent claims. ETSI TS 125 322 further teaches the transmitting window size is varied to a size which allows previously received data stored in the receiving buffer to be arranged in sequence without said additional data being lost in the receiving buffer. (pg. 15 4.2.1.3.1; 4.2.1.3.2)

## - In reference to claim 34

The combination of ETSITS 125 322 and Le et al. teaches a system and method that substantially, covers all limitations of the parent claims. ETSITS 125 322 further

Art Unit: 2619

teaches adjusting a window size of the receiving buffer based on the window size control information. (pg. 36; 9.2.2.11.8)

- In reference to claim 35

The combination of ETSI TS 125 322 and Le et al. teaches a system and method that substantially covers all limitations of the parent claims. ETSI TS 125 322 further teaches the varied window size of the receiving buffer (pg. 36 9.2.211.8) can be adjusted to be equal to the transmitting window size (pg. 33 9.2.2.11.3; 9.4) varied based on the window size control information.

# Response to Arguments

Applicant's arguments filed 04/25/2008 have been fully considered but they are not persuasive.

- In the Remarks on pg. 11 of the amendment, the Applicant contends that the cited references do not teach that the window size control information includes window size upward setting information, window size maintaining information, window size downward setting information and is transmitted simultaneously with acknowledgement information.
- The Examiner respectfully disagrees. In the ETSI publication, Figure 9.4
  explicitly shows a STATUS PDU containing multiple super fields (pg. 25). As
  later explained in the ETSI publication, the super fields may include an ACK
  field (pg. 32 9.2.2.11.2) and a window size field (pg. 33 9.2.2.11.3). The

Art Unit: 2619

window size field contains information for setting the window size of the receiving window. The window size may be set either upward, downward or maintained. The STATUS PDU containing both the window control information and acknowledgement information is then simultaneously transmitted from a receiver entity to a transmitter entity.

# Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to BRIAN ROBERTS whose telephone number is (571)272-3095. The examiner can normally be reached on M-F 10:00-7:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Wing Chan can be reached on (571) 272-7493. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Art Unit: 2619

/Gregory B Sefcheck/ Examiner, Art Unit 2619 7-1-2008

BSR 06/30/2008